

The KaMoGa Style

EMiC 7.1 Home Entertainment System

Featuring a sleek and small case design, the KaMoGa series allow easy installation on yacht and cruise ship, delivering the highest quality sound to rock your boat for as long as you choose to ride the waves.



The first of its kind that hubs all your Karaoke, Movies and Gaming under one roof with major advanced Dolby/DTS/4K Pass-Through features, eight programmable DSP pre-sets and more.

Be sure to indulge in a luxurious ride with KaMoGa... Sing to your heart's content; Enjoy a visual feast at the comfort of your yacht; The one and only satellite speakers and a subwoofer that surrounds you with a full spectrum soundscape... experience The Experience, the KaMoGa style...

📍 61 Ubi Road 1, #01-16 Oxley Bizhub 1, Singapore 408727

✉ sales@thunderstonektv.com

☎ +65 6702 6577 / +65 8717 1688 / +65 8281 6999

🌐 www.thunderstonektv.com

The KaMoGa Surround AV/DSP Receiver

EMiC MK520



TECHNICAL SPECIFICATIONS

POWER OUTPUT:

60 watts RMS per channel (all 7 channels driven), 120 watts RMS per channel (subwoofer driven)

HDMI:

HDMI 2.0, HDCP 2.2, 4K PASS-THROUGH

AUDIO INPUTS:

1 x USB Connection, 1 x Line-in (3.5mm Mini-Jack Analogue), 2 x Analogue L/R, 1 x Coaxial Digital Connection, 1 x Optical Digital Connection

VIDEO INPUTS: 3 x HDMI 2.0

MAIN AUDIO OUTPUTS:

7 Amplified Speaker Outputs, L+R preamp outs, 1 x subwoofer outputs

VIDEO OUTPUT:

1 x HDMI 2.0 with Audio Return Channel (ARC)

OTHER CONNECTIONS:

2 x 1/4" (6.35mm Microphone Input), Bluetooth 4.2

MAX POWER CONSUMPTION: 600W

STANDBY POWER CONSUMPTION: <0.5W

DIMENSIONS: W: 430, D: 268, H: 86 mm

WEIGHT: 24kg

ADDITIONAL DETAILS:

8 Programmable DSP Presets, Microphone Echo and Volume Control





10" KaMoGa SATELLITE AUDIO WOOFER

EMiC -7.1-SW

WOOFER SPECIFICATIONS

THD (Total Harmonic Distortion) : $\leq 5\%$ (1kHz, 1W)

MAX POWER CONSUMPTION: 120W

DRIVER UNITS: 1 x 10" Woofer

SENSITIVITY: 98dB

ENCLOSURE TYPE: Sealed

DIMENSIONS: W: 266, D: 290, H: 312 mm



2.5" KaMoGa T SATELLITE AUDIO SPEAKER

EMiC -7.1-SP

SPEAKER SPECIFICATIONS

THD (Total Harmonic Distortion) : $\leq 5\%$ (1kHz, 1W)

MAX POWER CONSUMPTION: 60W*7

DRIVER UNITS: 2 x 2.5" Tweeter

SENSITIVITY : 90dB

ENCLOSURE TYPE: Sealed

DIMENSIONS: W: 60, D: 83, H: 122 mm

The KaMoGa T Microphone

EMiC -7.1-Mic

MIRCROPHONE SPECIFICATIONS

DISPLAY: LCD PANEL

FREQUENCY: UHF 740-790 Mhz

DYNAMIC RANGE: 100dB

THD (Total Harmonic Distortion) : $\leq 5\%$ (1kHz, 1W)

WORKING RANGE: About 50m (without obstacle)

BATTERY LIFE: Approx. 8 hours

BATTERY POWER: DC 2 x 1.5V AA

