

SPEAKERS 7a



LVA-119

280W , 580 W RMS
13.5KG

LIVE
& VOCAL

2x3" Tweeters


4x2.5" Mid

1x10" Base

80hm
280W
560W(RMS)
95dB (Max Vol)
30 Kilograms
310 x 525 x 270 (mm)

"Warm", "Clear" Boasting on your mids. Makes vocals feel closer to you. In Thunderstone, we craft speakers, sing and feel with our hearts. With its 10" Base Cone, it reaches to the lowest frequency possible of 34Hz, giving you your "thump" on your music. Emphasising on the Mids, we have 4 pcs of 2.5" Cones. Each enhancing your vocals and brighten them up. To top it further, we have the 2 pcs of 3" tweeter cones that gives you the crisps of music delivering up to 20Khz .

In Thunderstone we know how to Sing thats why we can feel how you felt.



Hanging Instructions

Please use LVA Speaker brackets. Avoid mounting close to walls. Leave a 3 inch distance from walls

Sensitivity 1W to 1m, f> 80 Hz 94 dB SPL 94 dB SPL (1)
Maximum continuous level to 1m, (f > 80 Hz) 105 dB SPL
Peak continuous level to 1m (f > 80 Hz) 112 dB SPL
Coverage angles 120° Conical (2)
Nominal impedance 8 Ohm
Construction and characteristics
Cabinet 12 mm MDF

Passive crossovers Air-core inductors, paper capacitors, wound resistors
Overload protection Thermal circuit breaker with automatic reload
Finish black paint (LVA119B)
Front panel Black stretched Jersey (LVA119SJ),
Connectors Dual binding posts (LVA119)

*Tip: Constantly use your speakers as it will soften the rubberise ring attached to the driver cone. Rubber may become brittle for unattended use